

### **Development and Resource Management Department Building and Safety Services Division**

APPLICATION FOR DEMOLITION PERMIT				
Today's Date	Site Address			
Structure(s) to be demolished is/are: (Check	c all that apply)			
☐ Single Family Residence(s)	☐ Multi-Family Residence(s) ☐ Commercial			
Address/Location of demolition debris disp	osal			
Applicant Name	Phone Number			
Address	City, State and Zip			
Property Owner	Phone Number			
Address	City, State and Zip			
<ol> <li>and Excavation Certification Form.</li> <li>A Demolition Release Certification Formauthorized staff.</li> <li>A site plan, drawn to scale, which clear East and West property lines.</li> <li>A signature from authorized staff at the existing entitlement application(s) are</li> <li>A signature from the Historic Preservathistorical significance. (Signature Black)</li> </ol>	ation Division indicating that the structure(s) proposed for demolition are not of			
entitlement application(s), if any."				
Planning Division Public Counter Staff Sign "Structure(s) proposed for demolition are no	ot considered to be of historical significance."			
Historic Preservation Representative	Date			
BSD Staff Member				



### DEVELOPMENT AND RESOURCE MANAGEMENT DEPARTMENT BUILDING AND SAFETY SERVICES DIVISION

# CONDITIONS TO BE AGREED TO BY ALL PERSONS MAKING APPLICATION FOR DEMOLITION PERMIT

Any person requesting an application for a Demolition Permit shall agree to comply with section 11-218, DEBRIS AND EXCAVATIONS, of the Fresno Municipal Code:

#### Section 11-218. DEBRIS AND EXCAVATIONS.

It shall be the duty of any person to whom a permit issued for demolition or for the removal of any building, or any section or portion of any building pursuant to the provisions of this article, and of any person leasing, owning, or occupying or controlling any lot or parcel of ground from which a building is removed or demolished to remove all weeds, concrete or stone foundations, flat concrete, concrete patios, masonry walls, garage floors, driveways, and similar structures and all loose, miscellaneous, and useless material, from such lot or parcel of ground, and to properly cap the sanitary sewer house connection, and to properly fill or otherwise protect all basements, cellars, septic tanks, wells, and other excavations, and said lot or parcel shall be left level and in condition to be disked for control of weeds.


It shall be also understood that if any trees are allowed to remain, limbs shall be kept trimmed to provide a minimum clearance of 10 feet above the adjacent ground level to allow for disking as described in FMC section 11-218.

I hereby certify that on this _	· · · · · · · · · · · · · · · · · · ·		I have read,
understand, and agree to abid	e by the provisions of the above statemen	nt.	
	JOB ADDRESS		
APPLICANT'S NAME (1	PLEASE PRINT) APPLICANT	T'S SIGNATURE	



## DEVELOPMENT AND RESOURCE MANAGEMENT DEPARTMENT BUILDING AND SAFETY SERVICES DIVISION

### **REQUIREMENTS FOR PEDESTRIAN PROTECTION**



### When "h" is less than or equal to 8 feet:

- And "d" is 5 feet or more: No Protection is required. (*Table 3306.1 of 2010 California Building Code*)
- And "d" is less than 5 feet: Provide a substantially constructed railing or fence not less than 42 inches in height between the walkway and the building, and sufficient to direct pedestrians around construction areas.

(Section 3306.4 of 2010 California Building Code)

#### When "h" is greater than 8 feet:

- And "d" is 5 feet or more but greater than ½ the height: No Protection is required. (*Table 3306.1 of 2010 California Building Code*)
- And "d" is 5 feet or more; but between ¼ and ½ the height: Provide a solid fence or barrier a minimum 8 feet in height, placed on the side of the walkway nearest the construction. Barriers shall extend the entire length of the construction site. Openings in barriers shall be protected by doors which are normally kept closed.

(Table 3306.1 and Section 3306.5 of 2010 California Building Code)

- And "d" is 5 feet or more; but more than ½ the height: Provide a solid fence or barrier and covered walkway. The covered walkway shall have a clear height of 8 feet measured from the floor surface to the canopy overhead. Adequate lighting shall be provided at all times. (Table 3306.1 and Section 3306.7 of 2010 California Building Code)
- And "d" is less than 5 feet: Provide a solid fence or barrier and covered walkway. The covered walkway shall have a clear height of 8 feet measured from the floor surface to the canopy overhead. Adequate lighting shall be provided at all times.

(Table 3306.1 and Section 3306.7 of 2010 California Building Code)

All barriers shall be designed to conform to the requirements of section 3306.5 and 3306.6 of the 2010 California Building Code.

All covered walkways shall be designed to conform to the requirements of section 3306.7 of the 2010 California Building Code.